

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 794 727 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
20.08.2003 Bulletin 2003/34

(51) Int Cl.7: **A61B 5/00**

(21) Application number: **95926066.2**

(86) International application number:
PCT/SE95/00806

(22) Date of filing: **29.06.1995**

(87) International publication number:
WO 96/002183 (01.02.1996 Gazette 1996/06)

(54) APPARATUS FOR MEASUREMENT OF EATING SPEED

VORRICHTUNG ZUM MESSEN DER NAHRUNGS-AUFNAHME PRO ZEITEINHEIT

APPAREIL DE MESURE DE LA VITESSE D'INGESTION

(84) Designated Contracting States:
BE CH DE DK FR GB LI NL

(30) Priority: **15.07.1994 SE 9402488**

(43) Date of publication of application:
17.09.1997 Bulletin 1997/38

(73) Proprietor: **Mandometer AB**
118 20 Stockholm (SE)

(72) Inventors:
• **Södersten, Per**
118 20 Stockholm (SE)
• **Berg, Cecilia**
118 20 Stockholm (SE)

(74) Representative: **Hansson, Sven A. et al**
Zacco Sweden AB
P.O. Box 23101
104 35 Stockholm (SE)

(56) References cited:

- **INTERNATIONAL JOURNAL OF OBESITY**, Volume 17, No. 9, 1993, A.J. HOLLAND, "Measurement of Excessive Appetite and Metabolic Changes in Prader-Willi Syndrome", pages 527-532.
- **KISSILEFF ET AL**: 'Universal eating monitor for continuous recording of solid or liquid consumption in man' **AM. J. PHYSIOL.** vol. 7, no. 1, 1980, pages R14 - R22
- **GREISSLER, H. G. AND PETZOLD Y. M.**: 'Psychophysical judgement and the process of perception', **SPRINGER VERLAG, BERLIN** article **BORG G.**: 'A category scale with ratio properties for intermodal and interindividual comparisons' * page 25 - page 34 *

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 794 727 B1

Description**Field of the Invention**

5 [0001] The present invention pertains to a measuring device for the simultaneous measurement of the rate of eating behaviour and the associated perception of satiety in a measuring object during the ingestion of food.

Description of related art

10 [0002] There is a long standing need to control food intake and body weight, because overweight and obesity, for instance, are serious health problems. Given this starting point it is of considerable importance to develop methods for the measuring of eating behaviour and the experience of satiety.

Rate of ingestive behaviour

15 [0003] Ingestive behaviour has been studied by Kissileff et al. (Kissileff HR, Klingsberg G, Van Itallie TB (1980), "Universal eating monitor for continuous recording of solid or liquid consumption in man", American Journal of Physiology 283: R14-R22), who used a device having the features of the preamble of claim 1. During a meal the computer recorded the weight reduction of the plate from which the food was eaten. Using this method, the rate of ingestion could be estimated. It was concluded that eating rate is stable within individuals and variable between individuals. This document does not teach a reference standard encompassing a group of "normal" eating individuals. Kissileff et al. (Kissileff HR, Thornton J, Becker E (1982), "A quadratic equation adequately describes the cumulative food intake curve in man", Appetite 3: 255-272), suggested that eating rate in man, measured with the above procedure, can be described using a quadratic function. No alternatives have been suggested. There is, however, no biological support or foundation for the hypothesized quadratic function. That is to say, there is no biological factor that controls the rate of ingestion such that, during a meal, the rate of ingestion can be described by a quadratic function, because of the variation in the biological factor. Measuring the rate of ingestion is of considerable importance, in as much as alteration in this rate may be causally related to the development of obesity (Hetherington M, Rolls B (1987) "Methods of investigating human eating behaviour. In: Toates FM, Rowlands NE (eds.): "Eating and Drinking", pp 77-109, Elsevier; Amsterdam)

Satiety

35 [0004] There is, however, an equally large interest in measuring and controlling satiety. A change in the perception of satiety can also be the reason for developing obesity. Conventionally, the person participating in an experiment is asked to estimate her/his satiety before and after a meal utilizing a visual analogue scale, that is to say the person uses paper and pen to note how intense, on a continuum from low to high, she/he experiences her/his level of satiety.

40 [0005] Psychophysical studies of the subjective estimation of work load have been performed by Borg (Borg G (1982), "A category scale with ratio properties for intermodal and interindividual comparisons", In: Greissler H-G, Petzold YM (eds): "Psychophysical Judgement and the Process of Perception", pp 25-34, Springer Verlag: Berlin). Borg constructed a scale, that generates data on the level of an interval scale, that is to say a scale with equal steps.

45 [0006] The document "Measurement of Excessive Appetite and Metabolic Changes in Prader-Willi Syndrome", Holland et al., International Journal of Obesity, 17, No. 9, 1993, pages 527-532 is based on a measurement, in a group of patients with the Prader-Willi Syndrome (PWS, excessive food intake), and a control group without eating disorders to register feelings of hunger. Both groups where consuming sandwiches and juice, feelings of hunger are measured through an analogue scale and blood was taken for estimation of for instance cholecystokinin (CCK).

50 [0007] The measurement of hunger feelings where taken from a scale of 10 cm and assessment of hunger was registered by the persons in both groups pointing on the scale, whereby the obtained cm measure, from a zero point, of the pointing was taken as a value for the feeling of hunger.

Summary of the disclosed invention

55 [0008] The present invention is based on an alternative and a further development of the measurement of eating rate, in that different rates of ingestion correspond to a biologically determined degree of satiety. Eating rate is measured utilizing the variables (weight of food, time) and for the quantification of satiety the interval scale of Borg is used. The invention makes use of reference standards (standard curves or curves of normality), obtained from research on healthy individuals. These curves reflect the average rate of ingestion that has been found statistically significant through the investigation of groups, differing in, for example, age and weight, within the population of men and women. The interval

scale of Borg is used to record satiety. At the same time as a person participating in an experiment eats from her/his plate, placed on the scale as described above, this judgement scale is displayed on a monitor. According to this scale the level of satiety can vary from very weak, which is equivalent to 0-0.5, to very strong, which is equivalent to 10.

[0009] The present invention provides a device having the features of claim 1 that allows, among others, the obese to gain access to a method for weight control. Overweight and obesity is a major health problem, and the overweight, therefore, have an obvious interest in such a device. Furthermore, the control of body weight and ingestive behaviour is of considerable importance to athletes and those engaged in sports. A method for the control of body weight and eating behaviour is also needed within clinical medicine to care for patients suffering from anorexia, bulimia and gastrointestinal discomfort, that is to say disorders related to the intake of food. Use of the present device is, however, probably not limited to these groups, but is likely to be of importance to those within the general public who are at risk to develop disorders of body weight control.

[0010] A device to assist in the control of body weight provides the individual with a possibility to control eating behaviour and the perception of satiety and, therefore, a method to control body weight. According to the invention, this is accomplished by the display of the reference standards mentioned above on a monitor or via a printing unit. The reference standards for eating behaviour and satiety as a function of eating rate are derived from biologically based mean values obtained through research on samples of individuals from the general population. Using this device, the individual is in a position to adapt her/his eating behaviour and perception of satiety to what, by definition, is normal through the selection of the proper reference values and by adapting her/his rate of ingestion to the reference value displayed on a medium, for example a monitor, in real time. The rate of ingestion of the individual is displayed simultaneously with the reference standard and the two are to overlap.

[0011] Persons participating in the development of the invention and displaying deviations from the reference standards with respect to eating behaviour and perception of satiety have considered themselves unable or ignorant as to how to eat and how to feel satiated. Therefore, a device in a system according to the invention should be of considerable importance to a user with a need to control her/his food intake.

[0012] The present invention makes possible, what has previously been unknown, simultaneous registration and display of rate of eating and, at the same time, adjustment of satiety to a standard of reference, shown at the same time as the eating rate of the person. An observer and/or a user is thus in a position to modify, correct, verify, investigate etc her/his ingestive behaviour in real time. Repeated measurements on a considerable number of men and women have shown that the present invention generates stable values and reacts to a biological challenge, deprivation of food, that is to say the time without food that has elapsed before the time of measurement.

[0013] To meet the object of the invention it also includes to measure the rate of ingestion of a person eating a meal. It utilizes a scale to measure the intake of food and a first means signal connected with the scale for communication, computing and visualization of signals and for storing previously computed signals. The first means provides at least one reference standard for rate of ingestion and, in connection with each standard, a related specific, biologically based, level of satiety. This standard is used for comparison, visualization and evaluation of the measures of food intake, which have been obtained and stored in the first means, and to make it possible to adjust to a change in the rate of eating. To this aim the following steps should be taken:

- choice of reference standard, via the first means, for rate of eating. The standard and its satiety scale is visualized to allow one or several observers, including the person ingesting the food, to monitor an ongoing measurement;
- placement of a second means, for storing the food, on the scale and the placement of food on this device;
- allowing the scale to stabilize;
- initiation of a period of measurement of rate of eating when the person eats the food from the second means, a moment at which each measure of the intake of food is stored, computed and visualised;
- food is replenished as needed to allow for continued measurement; and
- a modification of the rate of eating, based on the standard of reference in relation to the actual rate of eating during the meal, can be introduced during the period of measurement.

[0014] Moreover, the present invention includes the establishment of reference standards concerning the rate of eating and, correlatively, the development of satiety and the pattern of secretion of gastrointestinal hormones. Furthermore, the reference standards are based on the effects of deprivation of food on the rate of eating, the development of satiety and the pattern of secretion of gastrointestinal hormones, such that the perception of satiety will wane in correlation with declining levels of these hormones. Eating behaviour and the perception of satiety is tested anew as soon as the experience of satiety has resumed its initial value. The octapeptide of cholecystokinin (CCK-8), in particular, is a determinant of satiety such that its pattern of secretion and the level of deprivation of food affects the rate of eating to become negatively accelerated and the experience of satiety positively accelerated with an increase in deprivation. According to the above, reference standards will be developed based on repeated testing of groups of individuals, large enough to permit establishment of statistical significance.

[0015] Visualization of the reference standard of eating behaviour and the measured eating rate will mainly be through the same medium (a monitor, a printer or some such), so as to facilitate visual comparison by the observer. When needed the first means can deliver an evaluation of satiety during the period of measurement of choice, e.g. via the monitor. The second means is preferably a household device for serving food, that is to say a plate, a bowl or a serving plate.

[0016] To serve its purpose, the invention includes to register the rate of eating displayed by a measuring object during the periods of eating to be measured. It thus includes a scale for the measurement of food intake, and a first means, signal connected with the scale, for storing and computing signals and visualization of these stored and computed signals. A second means, for storage of food, is placed on the scale. The measuring object eats the food, whereby the scale detects the signals generated by the first means, which then delivers at least one standard of reference for eating rate and one standard of a biologically determined level of satiety, and its associated numerical value. The reference standards will be utilized for comparison, evaluation and visualization together with the measures delivered by the scale and stored in the first means, thus allowing measures to compensate and change the rate of eating.

[0017] As mentioned above, a display of the reference standard and the recorded rate of eating can be made through the same medium to facilitate visual comparison for the observer and to make possible that the first means deliver an evaluation of the level of satiety and eating rate during any period of measurement. For example, through, par preference, a cartesian system of coordinates displayed on a monitor the satiety scale will be related to the reference standard of eating rate along with the recorded rate of eating (Fig. 3, below).

[0018] In the present embodiment, the scale is a peripheral device in relation to the computer.

[0019] In a further embodiment, the first means is a computer and the scale is integrated with a central unit in the computer.

[0020] According to another embodiment the central unit consists of a portable computer with the scale integrated, that is to say the keys have been replaced by the scale. The scale is internally and serially connected to the computer.

[0021] Placement of a second means on the scale as described in the present arrangement and the enclosed patent claims, implies that the second means should be possible to disconnect or should be connected to the scale as described further below.

Brief description of the drawings

[0022] The invention will be described in the following by reference to non limiting embodiments illustrated in the associated figures. For equivalent references between figures the same reference numerals will be used.

Fig. 1 shows a graphical example of an estimated level of satiety of a person tested under varying conditions using the scale of satiety according to the invention;

Fig. 2 shows a method including a computer system in which a scale is a peripheral part of the computer system;

Fig. 3 shows a display on a monitor with a standard curve of reference including a scale of satiety and an overlapping curve with actual measures of eating rate from an object of measurement from a test according to the invention;

Fig. 4 shows filtering of errors according to the invention; and

Fig. 5 shows a scale that has been integrated with a portable computer according to the invention.

Detailed description of preferred embodiments

[0023] According to the scientific papers mentioned above and to ongoing research in our laboratory, aiming at mathematical models of eating behaviour and the perception of satiety, there is no a priori reason for the selection of any mathematical model in particular, for example a quadratic model. This appears particularly true considering the great interindividual biological variability. Furthermore, a quadratic equation has not been found of optimal fit.

[0024] Because the factors that control the rate of eating and the perception of satiety are largely unknown models of eating behaviour and satiety should rely on biologically based hypotheses. Two biological factors of interest are the level of deprivation of food and the pattern of secretion of gastrointestinal hormones, in particular that of the octapeptide of cholecystokinin (CCK-8). The degree of deprivation should be varied and the eating behaviour and the perception of satiety should be related to the secretion of CCK-8 so that the decline in the level of satiation is measured and correlated to the concentration of CCK-8 in the blood. The eating behaviour and the perception of satiety is tested once more as soon as the level of satiety has returned to its basal value.

[0025] According to one hypothesis, which is the basis of the present invention, eating behaviour is determined by the level of deprivation and by CCK-8, such that the rate of eating is negatively accelerated after a long period of deprivation and that the perception of satiety is positively accelerated as shown by a graphical display of a curve. Studies on animals have demonstrated such a relationship between the duration of satiety and blood levels of CCK-8.

[0026] To allow establishment of standards of reference for eating behaviour, rate of eating and perception of satiety data will be collected from large groups of girls, boys, women and men. This will make possible quantitative description of behaviour and perception in all age groups of the population under the conditions discussed above.

[0027] An example of repeated estimation of satiety using the presently discussed rating scale is shown in Fig. 1, which is based on measures taken from an individual tested three times under the same conditions and a fourth time when the individual had abstained from dinner on the preceding day. The curves confirm the findings of Kissileff et al. (1980), that showed that eating behaviour is relatively consistent within individuals.

[0028] Fig. 2 shows a measuring device 10 with a first means 12, in this case a computing system, with a computer 14 and a peripheral equipment, including a key panel 16, a mouse 18, a track ball or a pointing device (not shown), a monitor 20 and a printer 22. The scale 24, that is included in the measuring device, is also peripheral to the computing system 12 according to the invention signal connected to the computing system 12, for example via the serial communication port. Signal connected implies that the connection, apart from being mediated via a cable, may be wire less by means of known technology (not shown), for example infrared, radio or the like technology. The scale 24, preferably a digital one although others are conceivable, need not be connected to the computer by any special adaptation. An analogous scale demands an adaptation device for sampling, quantification and analogue/digital conversion.

[0029] Protocols and the of the present invention do not demand new technology of computing or communication. The required technology of the present invention is known to those skilled in the art of computer technology and need not be elaborated here. Any computing system, that is available on the market, e.g. PC; Macintosh, portable computers or other, can be adapted. However, the method to utilize the invention and the measuring device, the computer system included, is a unique innovation.

[0030] Utilization of the measuring device 10 requires a second means 26 for the presentation of food, from which the user and measuring object 28, for example an athlete preparing for a big athletic competition, ingests food. It is possible for the athletic supervisor to participate as an observer. This means 26 is, most suitably, a common piece of household, such as a plate, a bowl or a serving plate.

[0031] To carry out a test with the measuring device 10 the program that controls the measurement is started, for example via the mouse 18, the steering ball or the key panel 16. It is also possible to start measuring when the means 26 is placed on the scale 26. Thereafter, the above described method is started to complete a test. If placement of the means 26 does not initiate the measurement, the user places the means 26, i.e. the plate 26, on the scale, and, thereafter, starts the measurement and the selection of reference standards 30, solid line of eating behaviour in Fig. 3 via the mouse. The interval scale of satiety included in Fig. 3, which shows 8 of the 10 intervals. The satiety is recorded at specified time points of the curve of eating rate. The width of the intervals is dependent of the biologically based perception of satiety in relation to the proper reference standard. As mentioned satiety is determined by the rate of eating and mediated by the biological factors mentioned above.

[0032] A period of measurement can also be initiated via the key panel 16, but normally this is done only when retrieving data and when updating programs. The standard of reference will become visible on a picture medium that is connected to the device, in this case the monitor of the computing system 20. If the user or the observer wants it to run "blind" it might be feasible not to display the standard to the user but store it in the computer for printout for example via a printer or delayed printout and the associated evaluation of the obtained rates of ingestion in relation to the standard of reference or other evaluations, such as evaluation of rating of satiety and statistical analyses. "Blind" measurement can also be accomplished by turning the monitor 20 away from the measuring object and permit only the observer to follow it. After the start of a period of measurement and placement of the plate 26 on the scale the food (not shown), which is selected according to the reference standard, is placed on the plate, stabilization of the scale is allowed for some seconds and the user starts eating. The rate of ingestion, the dotted line in Fig. 3, is then displayed over or overlapping the standard of reference on the monitor 20 thus making comparison in real time immediately possible and allowing measures, such as modifying the rate of ingestion, for adapting to the reference standard to be taken. Addition of food is made with reference to the standard 30, for example by clicking the mouse at regular time intervals which results in a display of information on how much food should be provided. It is terminated preferably by lifting the plate 26 from the scale 24. The results of the measurement are stored internally in one or several files, for later use, in the central unit 14 or in an external storage medium via one of the communication ports of the central unit (not shown).

[0033] The scale 24 will be subjected to unwanted pushes and unbalance when in use. Therefore, the following measures will be taken:

- i) The proper starting weight will be ensured (including a reasonable tolerance, e.g. 1 g).
- ii) A weight below the previous will be rejected.
- iii) A weight above that of a mouthful will be rejected.

[0034] In the present example the weight of a mouthful is estimated to 25 g. When a meal is started the user serves

food until the proper amount of food, determined by the reference standard, has been served. Before starting to eat, however, the scale must be stable to ensure the correct starting weight. In the pseudo code for filtering of erroneous values, shown below, the reference weight, i.e. the preceding weight is referred to as (v_0) the recorded weight as (v_n) and the weight of a mouthful as (g).

Pseudo code:

IF ($v_n \geq v_0 - g$) AND ($v_n \leq v_0$) THEN

BEGIN

WRITE(resfile, v_n) 'store recorded weight in result file'

$v_0 = v_n$

END

[0035] In Fig. 4, cross marked points are erroneous measured and filtered away according to the algorithm in the pseudo code.

[0036] In another version of the computer system 12 according to the present invention with reference to Fig. 5 the central unit 14 consists of a portable computer 34 with a monitor 20. To serve its purpose, the portable computer 34 has been made "user-friendly" by means of a new and innovative re-construction, i.e. the key panel has been replaced by a digital scale, including a plate 36. The scale is internally and serially connected to the portable computer. Apart from that the modified measuring device with the portable computer 34 as the central unit 14 works identically with the measuring device 10 described above and according to the present invention. It is easily recognized that a key panel can be connected to the computer 34 via some of its communication ports as needed. Most commonly, however, the method including choice of reference standard 30, addition of food etc, is started via a mouse, track ball or pointing device.

[0037] It is also possible to have the second means 26 for serving food permanently connected or removable on the plate 36 of the scale 24. This applies to both versions of the design of the measuring device 10. This can be made possible by the use of a vacuum suction device, a magnetic device or an equivalent device for removable mounting. In the case of a permanent mounting of the second means 26 for serving food removal of the plate of the scale 36 makes this possible.

[0038] The embodiments of the present invention described above are not intended to limit variations within the scope of the invention as defined by the appended claims.

Claims

1. A device (10) for measuring rate of eating (32) of an object of measurement (28) ingesting food, comprising a scale (24) for measuring of food intake, first means (12) which is signal connected, through a connection mediated through a cable or wireless, to said scale for storage of signals, computing of signals and visualization (20, 22) of stored and computed signals, second means (24) placed on the scale used for storage of the food to be consumed by said object of measurement (28), said scale being adapted to register the intake of food by means of said first means (12), **characterized in that** said first means (12) is adapted to provide at least one reference standard curve (30) for the rate of eating and, correlatively, the development of satiety and the pattern of gastrointestinal hormones, each such standard being developed based on repeated testing of groups of individuals and providing a biologically determined level of satiety and its associated scale of Borg for the quantification of satiety, which standard (30) of rate of eating is utilized for comparison, visualization (20, 22) and evaluation along with the actual measures of eating rate obtained from the scale and stored in said first means (12), and said standard allowing measures to be taken, in real time, to adjust the rate of eating (32) for adapting to the reference standard.
2. A device (10) according to claim 1, **characterized in that** visualization (20, 22) of said reference standards (30) and said recorded rate of eating (32) is displayed on the same medium in order to facilitate visual comparison.
3. A device (10) according to claims 1 and 2, **characterized in that** said first means (12) is adapted to provide an

evaluation of the level of satiety and/or the rate of eating during any period of measurement.

4. A device (10) according to one of claims 1- 3, **characterized in that** said first means (12) is a computer system.
5. A device (10) according to claim 4, **characterized in that** said scale (24) is integrated with a central unit (14) in said computer system.
6. A device (10) according to claim 5, **characterized in that** said central unit (14) is a portable computer (34).
7. A device (10) according to claim 4, **characterized in that** said scale (24) is a peripheral part in the computer system.
8. A device (10) according to claims 1-7, **characterized in that** said second means (26) is a piece of household equipment for serving food.

Patentansprüche

1. Vorrichtung (10) zur Messung der Essgeschwindigkeit (32) einer essenden Testperson, mit einer Waage (24) zur Messung der Essenseinnahme, einen ersten, über eine kabelgebundene oder drahtlose Signalverbindung mit der Waage verbundenen Mittel (12) zur Speicherung von Signalen, zur Verarbeitung von Signalen und zur Visualisierung (20, 22) der gespeicherten und verarbeiteten Signale, einen zweiten, auf der Waage aufliegenden Mittel (24) zur Aufbewahrung des von der Testperson (28) zu verzehrenden Essens, wobei die Waage in der Lage ist, die Nahrungseinnahme über die genannten ersten Mittel (12) zu erfassen, **dadurch gekennzeichnet, dass** das erste Mittel (12) in der Lage ist, mindestens eine Standard-Bezugskurve (30) für die Essgeschwindigkeit und korrelativ dazu den Verlauf der Sättigung sowie die Zusammensetzung der Gastrointestinalhormone zu liefern, wobei jeder solche Standard auf der Basis wiederholten Testens von Personengruppen entwickelt wird und einen biologisch bestimmten Sättigungsgrad sowie eine diesem zugeordnete Borg-Skala zur Quantifizierung der Sättigung zur Verfügung stellt, der Standard (30) für die Essgeschwindigkeit zum Vergleich, zur Visualisierung (20, 22) und zur Auswertung zusammen mit der durch die Waage tatsächlich gemessenen und in den ersten Mitteln (12) gespeicherten Essgeschwindigkeit dient, und dieser Standard in Echtzeit Massnahmen zu ergreifen gestattet, um die Essgeschwindigkeit (32) an den Bezugsstandard anzupassen.
2. Vorrichtung (10) nach Anspruch 1, **dadurch gekennzeichnet, dass** die Visualisierung (20, 22) der Bezugsstandards (30) und der genannten aufgezeichneten Essgeschwindigkeit (32) auf demselben Medium angezeigt wird, um den visuellen Vergleich zu erleichtern.
3. Vorrichtung (10) nach den Ansprüchen 1 und 2, **dadurch gekennzeichnet, dass** das genannte erste Mittel (12) in der Lage ist, während einer beliebigen Messperiode eine Auswertung des Sättigungsgrads und/oder der Essgeschwindigkeit zu liefern.
4. Vorrichtung (10) nach einem der Ansprüche 1 bis 3, **dadurch gekennzeichnet, dass** das genannte erste Mittel (12) ein Computersystem ist.
5. Vorrichtung (10) nach Anspruch 4, **dadurch gekennzeichnet, dass** die Waage (24) in eine Zentraleinheit (14) des Computersystems integriert ist.
6. Vorrichtung (10) nach Anspruch 5, **dadurch gekennzeichnet, dass** die Zentraleinheit (14) ein tragbarer Computer (34) ist.
7. Vorrichtung (10) nach Anspruch 4, **dadurch gekennzeichnet, dass** die Waage (24) ein Peripheriegerät des Computersystems ist.
8. Vorrichtung (10) nach einem der Ansprüche 1 bis 7, **dadurch gekennzeichnet, dass** das zweite Mittel (26) ein Haushaltsgegenstand zum Servieren von Speisen ist.

Revendications

1. Dispositif (10) de mesure du taux d'ingestion (32) d'un sujet de mesure (28) qui mange, comprenant une balance (24) pour mesurer l'ingestion des aliments, un premier moyen (12) relié par une connexion à signaux moyennant un câble ou sans fil à ladite balance pour la mémorisation de signaux, le traitement de signaux et la visualisation (20, 22) des signaux mémorisés et traités, un deuxième moyen (24) placé sur la balance et servant au stockage des aliments à consommer par ledit sujet de mesure (28), ladite balance étant adaptée à enregistrer l'ingestion des aliments par l'intermédiaire dudit premier moyen (12), **caractérisé en ce que** ledit premier moyen (12) est adapté à fournir au moins une courbe standard de référence (30) du taux d'ingestion et corrélativement le développement de la satiété et de la composition des hormones gastro-intestinales, chacun de tel standard étant développé sur la base de l'examen répété de groupes d'individus et fournissant un degré de satiété biologiquement déterminé et l'échelle de Borg y associée pour la quantification de la satiété, lequel standard (30) du taux d'ingestion est utilisé pour la comparaison, la visualisation (20, 22) et l'évaluation conjointement aux mesures effectives du taux d'ingestion obtenues de la balance et mémorisées dans ledit premier moyen (12), et ledit standard permettant de prendre en temps réel des mesures pour ajuster le taux d'ingestion (32) en vue de l'adapter au standard de référence.
2. Dispositif (10) selon la revendication 1, **caractérisé en ce que** la visualisation (20, 22) desdits standards de référence (30) et dudit taux d'ingestion (32) enregistré sont affichés sur le même affichage afin de faciliter la comparaison visuelle.
3. Dispositif (10) selon les revendications 1 et 2, **caractérisé en ce que** ledit premier moyen (12) est adapté à fournir une évaluation du degré de satiété et/ou du taux d'ingestion pendant une période de mesure quelconque.
4. Dispositif (10) selon l'une des revendications 1 à 3, **caractérisé en ce que** ledit premier moyen (12) est un système d'ordinateur.
5. Dispositif (10) selon la revendication 4, **caractérisé en ce que** ladite balance (24) est intégrée dans une unité centrale (14) dudit système d'ordinateur.
6. Dispositif (10) selon la revendication 5, **caractérisé en ce que** ladite unité centrale (14) est un ordinateur portable (34).
7. Dispositif (10) selon la revendication 4, **caractérisé en ce que** ladite balance (24) est un élément périphérique du système d'ordinateur.
8. Dispositif (10) selon l'une des revendications 1 à 7, **caractérisé en ce que** ledit deuxième moyen (26) est un objet ménager pour le service d'aliments.




FIG.1




FIG.2




FIG.3




FIG.4




FIG.5